

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifierTrade name: **Solder liquid "ZD pro"**

UFI: SRD8-A016-V00E-SS0S

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Application of the substance / the mixture *Soldering flux***1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

FELDER GMBH

Im Lipperfeld 11

D-46047 Oberhausen

Tel.: 0208/8 50 35-0

Fax.: 0208/2 60 80

<http://www.felder.de>e-mail: info@felder.de**Further information obtainable from:**

lab

(mo-thu. 8:00 a.m. - 4:00 p.m./ fr. 8:00 a.m. - 1:00 p.m.)

email: mprobst@felder.de**1.4 Emergency telephone number:**

24-hour emergency information:

Giftnotruf Berlin, counselling in German and English

Phone: (030) 30686 700

EuPCS: PC-TEC-24

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture**Classification according to Regulation (EC) No 1272/2008**

GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS05 GHS07 GHS09

Signal word *Danger***Hazard-determining components of labelling:***zinc chloride**hydrogen chloride*

(Contd. on page 2)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: Solder liquid "ZD pro"

(Contd. of page 1)

Hazard statements

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Labelling of packages where the contents do not exceed 125 ml**Hazard pictograms**

GHS05 GHS07 GHS09

Signal word Danger**Hazard-determining components of labelling:**

zinc chloride

hydrogen chloride

Hazard statements

H314 Causes severe skin burns and eye damage.

Precautionary statements

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Description: Mixture: consisting of the following components.

Dangerous components:

CAS: 7646-85-7 EINECS: 231-592-0 Index number: 030-003-00-2 Reg.nr.: 01-2119472431-44	zinc chloride ☞ Skin Corr. 1B, H314 ☞ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ☞ Acute Tox. 4, H302 Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	<50%
CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44	2-(2-butoxyethoxy)ethanol ☞ Eye Irrit. 2, H319	<50%
CAS: 7647-01-0 EINECS: 231-595-7 Index number: 017-002-00-2 Reg.nr.: HCl Gas : 01-2119484862-27	hydrogen chloride ☞ Met. Corr. 1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318 ☞ Acute Tox. 4, H302; STOT SE 3, H335 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 25 % Skin Irrit. 2; H315: 10 % ≤ C < 25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 % STOT SE 3; H335: C ≥ 10 %	<25%

(Contd. on page 3)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: Solder liquid "ZD pro"

CAS: 12125-02-9 EINECS: 235-186-4 Index number: 017-014-00-8 Reg.nr.: 01-2119487950-27	ammonium chloride ⚠ Acute Tox. 4, H302; Eye Irrit. 2, H319	(Contd. of page 2) <10%
---	---	----------------------------

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Seek medical treatment.

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water.

Protect unharmed eye.

Seek medical treatment.

After swallowing:

Rinse out mouth and then drink plenty of water.

Seek medical treatment.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

Hazards Danger of gastric perforation.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray.

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Hydrogen chloride (HCl)

5.3 Advice for firefighters

Protective equipment: Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: Solder liquid "ZD pro"

(Contd. of page 3)

Prevent formation of aerosols.

Information about fire - and explosion protection: No special measures required.**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** No special requirements.**Information about storage in one common storage facility:**

Store separately from metals.

Store away from foodstuffs.

Further information about storage conditions: Keep container tightly sealed.**Storage class:** 8 A**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****112-34-5 2-(2-butoxyethoxy)ethanol**

IOELV (EU)	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
AGW (Germany)	Long-term value: 67 mg/m ³ , 10 ppm 1.5(I);EU, DFG, Y, 11
WEL (Great Britain)	Short-term value: 101.2 mg/m ³ , 15 ppm Long-term value: 67.5 mg/m ³ , 10 ppm
OEL (Ireland)	Short-term value: 101.2 mg/m ³ , 12 ppm Long-term value: 67.5 mg/m ³ , 10 ppm IOELV

7647-01-0 hydrogen chloride

IOELV (EU)	Short-term value: 15 mg/m ³ , 10 ppm Long-term value: 8 mg/m ³ , 5 ppm
WES (Australia)	Ceiling limit: 7.5 mg/m ³ , 5 ppm
AGW (Germany)	Long-term value: 3 mg/m ³ , 2 ppm 2(I);DFG, EU, Y
WEL (Great Britain)	Short-term value: 8 mg/m ³ , 5 ppm Long-term value: 2 mg/m ³ , 1 ppm (gas and aerosol mists)
OEL (Ireland)	Short-term value: 15 mg/m ³ , 10 ppm Long-term value: 8 mg/m ³ , 5 ppm IOELV

12125-02-9 ammonium chloride

WES (Australia)	Short-term value: 20 mg/m ³ Long-term value: 10 mg/m ³ fume
WEL (Great Britain)	Short-term value: 20 mg/m ³ Long-term value: 10 mg/m ³
OEL (Ireland)	Short-term value: 20 mg/m ³ Long-term value: 10 mg/m ³

25322-68-3 Polyethylene glycol

AGW (Germany)	Long-term value: 200 E mg/m ³ 2(II);DFG, Y
---------------	--

Regulatory information

IOELV (EU): (EU) 2019/1831

AGW (Germany): TRGS 900

WEL (Great Britain): EH40/2020

OEL (Ireland): 2024 CoP for the Safety, Health and Welfare at Work

WES (Australia): Workplace exposure standards for airborne contaminants

recommended monitoring procedures in accordance with 2020/878/EU no. 8.1.2:

112-34-5 2-(2-butoxyethoxy)ethanol: BIA 6450(D)

7647-01-0 hydrogen chlorid: BIA 6640(D), MTA/MA-019/A90(ESP), OSHA ID-174SG(E), MétroPol Fiche 009 Anions minéraux(F)

12125-02-9 ammonium chloride: OSHA, ID-188 (E) "ammonia"

(Contd. on page 5)

EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: Solder liquid "ZD pro"

(Contd. of page 4)

DNELs		
7646-85-7 zinc chloride		
Dermal	DNEL, kurzzeit	8.3 mg/kg /KG/Tag (worker)
Inhalative	DNEL, kurzzeit	1 mg/m ³ (worker)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Appropriate engineering controls:

Ensure adequate ventilation.

Remove the fumes by means of suitable suction devices.

Ensure adequate ventilation.

Remove the fumes by suitable suction devices.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter B

Hand protection



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.6 mm

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Value for the permeation: Level ≤ 6

As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR

Not suitable are gloves made of the following materials: Natural rubber, NR

Eye/face protection



Tightly sealed goggles

Body protection: Acid resistant protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour:	Dark yellow
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	100 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	0.9 Vol %
Upper:	5.9 Vol %
Flash point:	98 °C
Auto-ignition temperature:	225 °C

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: Solder liquid "ZD pro"

(Contd. of page 5)

Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	23 hPa
Density and/or relative density	
Density at 20 °C:	1.3 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	
Organic solvents:	31.5 %
Water:	14.8 %
VOC (EC)	31.50 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions**
Reacts with various metals.
Development of corrosive gases/vapours.
- 10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:** Corrosive gases/vapours

(Contd. on page 7)
EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: Solder liquid "ZD pro"

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	2,032-2,200 mg/kg
------	------	-------------------

7646-85-7 zinc chloride

Oral	LD50	1,100-1,260 mg/kg (rat)
------	------	-------------------------

Primary irritant effect:

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability Some of the components are not readily biodegradable

Other information: The product is not easily biodegradable.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Very toxic for fish

Additional ecological information:

General notes:

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dilute the concentrate with water and then neutralise with a suitable alkaline material (caustic soda, lime).

European waste catalogue

06 03 13*: solid salts and solutions containing heavy metals

HP 6: acute toxicity

HP 8: corrosive

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: Solder liquid "ZD pro"

(Contd. of page 7)

HP 14: ecotoxic

cleaned sales packaging:

15 01 02: packaging made of plastic

outer packaging:

15 01 01: packaging made of paper and cardboard

Uncleaned packaging:

15 01 10*: Packaging containing residues of dangerous substances or contaminated by dangerous substances

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN3264

14.2 UN proper shipping name

ADR

3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
(HYDROCHLORIC ACID, ZINC CHLORIDE),
ENVIRONMENTALLY HAZARDOUS

IMDG

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
(HYDROCHLORIC ACID, ZINC CHLORIDE), MARINE
POLLUTANT

IATA

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
(HYDROCHLORIC ACID, ZINC CHLORIDE)**14.3 Transport hazard class(es)**

ADR, IMDG



Class

8 Corrosive substances.

Label

8

IATA



Class

8 Corrosive substances.

Label

8

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:

Product contains environmentally hazardous substances: zinc chloride

Marine pollutant:

Yes

Symbol (fish and tree)

Symbol (fish and tree)

Special marking (ADR):

Warning: Corrosive substances.

14.6 Special precautions for user

Hazard identification number (Kemler code):

80

EMS Number:

F-A,S-B

Segregation groups

(SGG1) Acids

Stowage Category

B

Stowage Code

SW2 Clear of living quarters.

14.7 Maritime transport in bulk according to IMO

instruments

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

1L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Transport category

2

Tunnel restriction code

E

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: Solder liquid "ZD pro"

(Contd. of page 8)

IMDG**Limited quantities (LQ)**

1L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(HYDROCHLORIC ACID, ZINC CHLORIDE), 8, II,

ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2012/18/EU****Named dangerous substances - ANNEX I** *None of the ingredients is listed.***Seveso category E1** *Hazardous to the Aquatic Environment***Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t**REGULATION (EU) 2019/1021 on persistent organic pollutants (POP)** *None of the ingredients are included.***REGULATION (EC) No 1907/2006 ANNEX XVII** *Conditions of restriction: 3, 55, 65***DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II***None of the ingredients is listed.***REGULATION (EU) 2019/1148****Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))***None of the ingredients is listed.***Annex II - REPORTABLE EXPLOSIVES PRECURSORS***None of the ingredients is listed.***Regulation (EC) No 273/2004 on drug precursors***None of the ingredients is listed.***Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors***None of the ingredients is listed.***National regulations:****Information about limitation of use:** *Employment restrictions concerning juveniles must be observed.***Waterhazard class:** *Water hazard class 3 (Self-assessment): extremely hazardous for water.***15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.***SECTION 16: Other information***This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.***Reasons for changes:**

05.01.2016: section 1.8, 15 adaptation to regulation 453/2010/EC, 830/2015/EU and 18/2012/EU

20.03.2017: section 8.1

03.07.2018: section 13

31.03.2020: section 1, 11

12.08.2020: section 1 UFI

25.05.2021: section 3, 15, 16

20.09.2021: Section 1, 15

20.01.2023: section 14, 15

17.04.2025: section 8, 9, 11

Information referred to in Annex I, point 1.3.4.2 of Regulation 1272/2008/EC:**Relevant phrases**H290 *May be corrosive to metals.*H302 *Harmful if swallowed.*H314 *Causes severe skin burns and eye damage.*H315 *Causes skin irritation.*

(Contd. on page 10)

— EU —

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 18.06.2025

Version number 10 (replaces version 9)

Revision: 17.04.2025

Trade name: Solder liquid "ZD pro"

(Contd. of page 9)

*H318 Causes serious eye damage.**H319 Causes serious eye irritation.**H335 May cause respiratory irritation.**H400 Very toxic to aquatic life.**H410 Very toxic to aquatic life with long lasting effects.***Contact: Dr. M. Probst****Version number of previous version: 9****Abbreviations and acronyms:***RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)**IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)**ICAO: International Civil Aviation Organisation**ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**VOC: Volatile Organic Compounds (USA, EU)**DNEL: Derived No-Effect Level (REACH)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**ATE: Acute toxicity estimate values**Met. Corr. 1: Corrosive to metals – Category 1**Acute Tox. 4: Acute toxicity – Category 4**Skin Corr. 1B: Skin corrosion/irritation – Category 1B**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1***Safety data sheet SD3037**