

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 10.07.2024

Version number 5

Revision: 10.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifierTrade name: **Lötöl ISO-Flux "Kolo"**

UFI: 3JM8-90JK-200H-1R1V

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Application of the substance / the mixture *Soldering flux***1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Felder GmbH
Im Lipperfeld 11
D-46047 Oberhausen

Tel.: +49 (0)208/ 85035-0

Fax.: +49 (0)208/ 26080

<http://www.felder.de>e-mail: info@felder.de**Further information obtainable from:**

lab

(mo-thu. 8:00 a.m. - 4:00 p.m./ fr. 8:00 a.m. - 1:00 p.m.)

email: mprobst@felder.de**1.4 Emergency telephone number: Tel: +49(0)208/ 85035-29**

EuPCS: PC-TEC-24

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture**Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 2 H225 *Highly flammable liquid and vapour.*

GHS08 health hazard

Repr. 2 H361d *Suspected of damaging the unborn child.*

GHS07

Eye Irrit. 2 H319 *Causes serious eye irritation.*STOT SE 3 H336 *May cause drowsiness or dizziness.***2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02 GHS07 GHS08

Signal word *Danger***Hazard-determining components of labelling:***propan-2-ol**2-methylpentane-2,4-diol***Hazard statements**H225 *Highly flammable liquid and vapour.*H319 *Causes serious eye irritation.*H361d *Suspected of damaging the unborn child.*H336 *May cause drowsiness or dizziness.*

(Contd. on page 2)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 10.07.2024

Version number 5

Revision: 10.07.2024

Trade name: Lötöl ISO-Flux "Kolo"

(Contd. of page 1)

Precautionary statements

- P101 *If medical advice is needed, have product container or label at hand.*
 P102 *Keep out of reach of children.*
 P103 *Read carefully and follow all instructions.*
 P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
 P303+P361+P353 *IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].*
 P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
 P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
 P405 *Store locked up.*
 P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

Labelling of packages where the contents do not exceed 125 ml**Hazard pictograms**

GHS02 GHS07 GHS08

Signal word *Danger***Hazard-determining components of labelling:**

propan-2-ol
2-methylpentane-2,4-diol

Hazard statements

H361d Suspected of damaging the unborn child.
H336 May cause drowsiness or dizziness.

Precautionary statements

- P101 *If medical advice is needed, have product container or label at hand.*
 P102 *Keep out of reach of children.*
 P103 *Read carefully and follow all instructions.*
 P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
 P405 *Store locked up.*
 P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** *Not applicable.***vPvB:** *Not applicable.***SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** *Mixture: consisting of the following components.*

Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	<i>propan-2-ol</i> 	50-100%
CAS: 107-41-5 EINECS: 203-489-0 Index number: 603-053-00-3 Reg.nr.: 01-2119539582-35	<i>2-methylpentane-2,4-diol</i> 	<5%

Additional information: *For the wording of the listed hazard phrases refer to section 16.***SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** *Take affected persons out into the fresh air.***After inhalation:** *Supply fresh air; consult doctor in case of complaints.***After skin contact:***Wash with polyethylene glycol and ethanol (2:1). Then wash thoroughly with water and soap.**Generally the product does not irritate the skin.*

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 10.07.2024

Version number 5

Revision: 10.07.2024

Trade name: Lötöl ISO-Flux "Kolo"

(Contd. of page 2)

After eye contact:*Seek medical treatment.**Rinse opened eye for several minutes under running water. Then consult a doctor.***After swallowing:***Rinse out mouth and then drink plenty of water.**Call for a doctor immediately.***4.2 Most important symptoms and effects, both acute and delayed** *No further relevant information available.***4.3 Indication of any immediate medical attention and special treatment needed***No further relevant information available.***SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:***Use fire extinguishing methods suitable to surrounding conditions.**CO₂, sand, extinguishing powder. Do not use water.**Alcohol resistant foam***For safety reasons unsuitable extinguishing agents:** *Water***5.2 Special hazards arising from the substance or mixture** *Can form explosive gas-air mixtures.***5.3 Advice for firefighters****Protective equipment:***Do not inhale explosion gases or combustion gases.**Wear self-contained respiratory protective device.***SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures***Wear protective equipment. Keep unprotected persons away.***6.2 Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.***6.3 Methods and material for containment and cleaning up:***Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Ensure adequate ventilation.**Do not flush with water or aqueous cleansing agents***6.4 Reference to other sections***See Section 7 for information on safe handling.**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.***SECTION 7: Handling and storage****7.1 Precautions for safe handling***Ensure good ventilation/exhaustion at the workplace.**Prevent formation of aerosols.**Keep away from heat and direct sunlight.***Information about fire - and explosion protection:***Keep ignition sources away - Do not smoke.**Protect against electrostatic charges.***7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:** *Store in a cool location.***Information about storage in one common storage facility:***Store away from foodstuffs.**Store away from flammable substances.***Further information about storage conditions:***Protect from frost.**Protect from heat and direct sunlight.**Store in cool, dry conditions in well sealed receptacles.***Storage class:** 3**7.3 Specific end use(s)** *No further relevant information available.*

(Contd. on page 4)

— EU —

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 10.07.2024

Version number 5

Revision: 10.07.2024

Trade name: Lötöl ISO-Flux "Kolo"

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

AGW (Germany)	Long-term value: 500 mg/m ³ , 200 ppm 2(II);DFG, Y
WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
OEL (Ireland)	Short-term value: 400 ppm Long-term value: 200 ppm Skin

107-41-5 2-methylpentane-2,4-diol

MAK (Germany)	Long-term value: 49 mg/m ³ , 10 ppm vgl. Abschn. Xc; Dampf und Aerosol
WEL (Great Britain)	Short-term value: 123 mg/m ³ , 25 ppm Long-term value: 123 mg/m ³ , 25 ppm
OEL (Ireland)	Short-term value: 125 mg/m ³ , 25 ppm

Regulatory information

AGW (Germany): TRGS 900

WEL (Great Britain): EH40/2020

OEL (Ireland): 2024 CoP for the Safety, Health and Welfare at Work

MAK (Germany): MAK- und BAT-Liste

recommended monitoring procedures in accordance with 2020/878/EU no. 8.1.2:

67-63-0 propan-2-ol: BIA 8415(D), MétroPol Fiche 077 Alcools en C3 à C8(F), MTA/MA-016/A89(ESP), DFG (D, E)
Solvent mixtures 6

107-41-5 2-methylpentane-2,4-diol: OSHA PV 2101(E) "Hexylene glycol"

Ingredients with biological limit values:

67-63-0 propan-2-ol

BGW (Germany)	25 mg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton
	25 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton

Regulatory information BGW (Germany): TRGS 903

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation.

Explosion protection required. Extinguish all open flames. Eliminate ignition sources. Avoid sparking.

Take measures against electrostatic charging. Earth all equipment.

Remove vapours using suitable extraction equipment.

Appropriate engineering controls:

Ensure adequate ventilation.

Explosion protection equipment required. Extinguish all open flames. Remove sources of ignition. avoid sparks.

Take precautionary measures against electrostatic charging. Ground all devices.

Removing the fumes by suitable suction devices.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter P2

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 10.07.2024

Version number 5

Revision: 10.07.2024

Trade name: Lötöl ISO-Flux "Kolo"

(Contd. of page 4)

Hand protection

Solvent resistant gloves



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.33 mm

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Value for the permeation: Level ≤ 6

Not suitable are gloves made of the following materials:

Natural rubber, NR

PVA gloves

Eyeface protection

Tightly sealed goggles

Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information**

Colour: Amber coloured

Odour: Characteristic

Boiling point or initial boiling point and boiling range 82 °C

Lower and upper explosion limit

Lower: 2.0 Vol %

Upper: 12.0 Vol %

Flash point: 13 °C

Auto-ignition temperature: 180 °C

pH: Not determined

Solubility

water: Not miscible or difficult to mix.

Density and/or relative densityDensity at 20 °C: 0.858 g/cm³**9.2 Other information****Appearance:**

Form: Fluid

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Solvent content:

Organic solvents: <80.0 %

VOC (EC) 70.00 %

Solids content: 25.0 %

Information with regard to physical hazard classes

Explosives: Void

Flammable gases: Void

Aerosols: Void

Oxidising gases: Void

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 10.07.2024

Version number 5

Revision: 10.07.2024

Trade name: Lötöl ISO-Flux "Kolo"

(Contd. of page 5)

Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability**
Thermal decomposition / conditions to be avoided:
 No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions** Forms flammable gases/fumes.
- 10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:**
 Flammable gases/vapours
 Aldehyde

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
Acute toxicity Based on available data, the classification criteria are not met.
Skin corrosion/irritation Based on available data, the classification criteria are not met.
Serious eye damage/irritation
 Causes serious eye irritation.
Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
Germ cell mutagenicity Based on available data, the classification criteria are not met.
Carcinogenicity Based on available data, the classification criteria are not met.
Reproductive toxicity
 Suspected of damaging the unborn child.
STOT-single exposure
 May cause drowsiness or dizziness.
STOT-repeated exposure Based on available data, the classification criteria are not met.
Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards**

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity**
Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment**
PBT: Not applicable.
vPvB: Not applicable.
- 12.6 Endocrine disrupting properties**
 The product does not contain substances with endocrine disrupting properties.

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 10.07.2024

Version number 5

Revision: 10.07.2024

Trade name: Lötöl ISO-Flux "Kolo"

(Contd. of page 6)

12.7 Other adverse effects**Additional ecological information:****General notes:***Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water**Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.***SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation***Must not be disposed together with household garbage. Do not allow product to reach sewage system.***European waste catalogue***07 01 04*: other organic solvents, washing liquids and mother liquors**HP3: Flammable**HP4: Irritant - skin irritation and eye damage**HP5: Specific Target Organ Toxicity (STOT)/Aspiration Toxicity**HP10: Toxic for reproduction**cleaned plastic can:**15 01 02: plastic packaging**overpack:**15 01 01: paper and cardboard packaging***Uncleaned packaging:** *15 01 10*: packaging containing residues of or contaminated by hazardous substances***Recommendation:** *Disposal must be made according to official regulations.***Recommended cleansing agents:***Rinse emptied can with alcohol, treat with alkaline cleaner and then rinse with water.***SECTION 14: Transport information****14.1 UN number or ID number****ADR, IMDG, IATA**

UN1219

14.2 UN proper shipping name**ADR**

1219 ISOPROPANOL (ISOPROPYL ALCOHOL) mixture

IMDG, IATA

ISOPROPANOL (ISOPROPYL ALCOHOL) mixture

14.3 Transport hazard class(es)**ADR, IMDG, IATA****Class**

3 Flammable liquids.

Label

3

14.4 Packing group**ADR, IMDG, IATA**

II

14.5 Environmental hazards:**Marine pollutant:**

No

14.6 Special precautions for user*Warning: Flammable liquids.***Hazard identification number (Kemler code):**

33

EMS Number:

F-E,S-D

Stowage Category

B

14.7 Maritime transport in bulk according to IMO instruments*Not applicable.***Transport/Additional information:****ADR****Limited quantities (LQ)**

1L

Excepted quantities (EQ)

Code: E2

*Maximum net quantity per inner packaging: 30 ml**Maximum net quantity per outer packaging: 500 ml***Transport category**

2

Tunnel restriction code

D/E

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 10.07.2024

Version number 5

Revision: 10.07.2024

Trade name: Lötöl ISO-Flux "Kolo"

(Contd. of page 7)

IMDG

Limited quantities (LQ)

1L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) MIXTURE,
3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I *None of the ingredients is listed.*

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EU) 2019/1021 on persistent organic pollutants (POP) *None of the ingredients are included.*REGULATION (EC) No 1907/2006 ANNEX XVII *Conditions of restriction: 3*

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS
--

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

*None of the ingredients is listed.***National regulations:**Information about limitation of use: *Employment restrictions concerning juveniles must be observed.*Waterhazard class: *Water hazard class 1 (Self-assessment): slightly hazardous for water.***15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.***Reasons for changes:**

26.08.2016: section 13

28.06.2018: section 11, 13

13.09.2021: section 1, 13, 15, 16

10.07.2024: section 2, 3, 11, 12, 13, 15

Information referred to in Annex I, point 1.3.4.2 of Regulation 1272/2008/EC:**Relevant phrases**H225 *Highly flammable liquid and vapour.*H315 *Causes skin irritation.*H319 *Causes serious eye irritation.*H336 *May cause drowsiness or dizziness.*H361d *Suspected of damaging the unborn child.***Contact:** *Dr. M. Probst***Abbreviations and acronyms:**RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*IATA-DGR: *Dangerous Goods Regulations by the "International Air Transport Association" (IATA)*ICAO: *International Civil Aviation Organisation*

(Contd. on page 9)

— EU —

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31 and 2020/878/
EU

Printing date 10.07.2024

Version number 5

Revision: 10.07.2024

Trade name: Lötöl ISO-Flux "Kolo"

(Contd. of page 8)

*ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**VOC: Volatile Organic Compounds (USA, EU)**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**ATE: Acute toxicity estimate values**Flam. Liq. 2: Flammable liquids – Category 2**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Repr. 2: Reproductive toxicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3***Safety data sheet SD3116**

EU
