

Safety data sheet
according to 1907/2006/EC, Article 31 and 2020/878/EU

Printing date 12.08.2021

Version number 6 (replaces version 5)

Revision: 12.08.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Kabelflussmittel ISO-Flux "KF-1"**
Cable flux ISO-Flux "KF-1"

UFI: 1UU8-A07A-300K-8RKC



1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Flux

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Felder GmbH
 Im Lipperfeld 11
 D-46047 Oberhausen

Tel.: +49 (0)208/ 85035-0

Fax.: +49 (0)208/ 26080

<http://www.felder.de>

e-mail: info@felder.de

Further information obtainable from:

lab

(mo-thu: 8:00 a.m. - 4:00 p.m./ fr: 8:00 a.m. - 1:00 p.m.)

email: mprobst@felder.de

1.4 Emergency telephone number:

Tel.: +49(0) 208/85035-29

(mo-thu: 08:00 a.m. -04:00 p.m.; fr: 08:00 a.m. - 01:00 p.m.)

EuPCs: PC-TEC-24

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

propan-2-ol

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 *If medical advice is needed, have product container or label at hand.*

P102 *Keep out of reach of children.*

P103 *Read carefully and follow all instructions.*

P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*

(Contd. on page 2)

EU

Safety data sheet
according to 1907/2006/EC, Article 31 and 2020/878/EU

Printing date 12.08.2021

Version number 6 (replaces version 5)

Revision: 12.08.2021

Trade name: Kabelflussmittel ISO-Flux "KF-1"
Cable flux ISO-Flux "KF-1"

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

propan-2-ol

Hazard statements

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture: consisting of the following components.

Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	50-100%
CAS: 506-59-2 EINECS: 208-046-5	dimethylammonium chloride Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Alcohol resistant foam

CO₂, sand, extinguishing powder. Do not use water.

(Contd. on page 3)

EU

Safety data sheet
according to 1907/2006/EC, Article 31 and 2020/878/EU

Printing date 12.08.2021

Version number 6 (replaces version 5)

Revision: 12.08.2021

Trade name: Kabelflussmittel ISO-Flux "KF-1"
Cable flux ISO-Flux "KF-1"

(Contd. of page 2)

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

AGW (Germany)	Long-term value: 500 mg/m ³ , 200 ppm 2(II);DFG, Y
WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
OEL (Ireland)	Short-term value: 400 ppm Long-term value: 200 ppm Sk

95-14-7 benzotriazole

MAK (Germany)	vgl.Abschn. Xc, Dampf und Aerosol
---------------	-----------------------------------

Regulatory information

AGW (Germany): TRGS 900

WEL (Great Britain): EH40/2020

(Contd. on page 4)

EU

Safety data sheet
according to 1907/2006/EC, Article 31 and 2020/878/EU

Printing date 12.08.2021

Version number 6 (replaces version 5)

Revision: 12.08.2021

Trade name: Kabelflussmittel ISO-Flux "KF-1"
Cable flux ISO-Flux "KF-1"

(Contd. of page 3)

OEL (Ireland): 2020 CoP for the Safety, Health and Welfare at Work

MAK (Germany): MAK- und BAT-Liste

recommended monitoring procedures in accordance with 2020/878/EU no. 8.1.2:

67-63-0 Propan-2-ol: BIA 8415(D), MétroPol Fiche 077 Alcohols en C3 à C8(F), MTA/MA-016/A89(ESP), DFG (D, E)
Solvent mixtures 6

Ingredients with biological limit values:

67-63-0 propan-2-ol

BGW (Germany)	25 mg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton
	25 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton

Regulatory information BGW (Germany): TRGS 903

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls

No further data; see item 7.

Ensure adequate ventilation.

Explosion protection required. Remove all open flames. Remove ignition sources. Avoid sparks.

Take precautionary measures against electrostatic charging. Ground all devices.

Remove the fumes by means of suitable suction devices.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Hand protection



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.33 mm

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Value for the permeation: Level ≤ 6

Eye/face protection



Tightly sealed goggles

Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour:

Colourless

Odour:

Characteristic

(Contd. on page 5)

EU

Safety data sheet
according to 1907/2006/EC, Article 31 and 2020/878/EU

Printing date 12.08.2021

Version number 6 (replaces version 5)

Revision: 12.08.2021

Trade name: Kabelflussmittel ISO-Flux "KF-1"
Cable flux ISO-Flux "KF-1"

(Contd. of page 4)

Odour threshold:	<i>Not determined.</i>
Melting point/freezing point:	<i>< -90 °C</i>
Boiling point or initial boiling point and boiling range	<i>82 °C</i>
Flammability	<i>Not applicable.</i>
Lower and upper explosion limit	
Lower:	<i>2.0 Vol %</i>
Upper:	<i>12.0 Vol %</i>
Flash point:	<i>13 °C</i>
Auto-ignition temperature:	<i>Product is not selfigniting.</i>
Decomposition temperature:	<i>Not determined.</i>
pH	<i>Not determined.</i>
Viscosity:	
Kinematic viscosity	<i>Not determined.</i>
Dynamic:	<i>Not determined.</i>
Solubility	
water:	<i>Not miscible or difficult to mix.</i>
Partition coefficient n-octanol/water (log value)	<i>Not determined.</i>
Vapour pressure at 20 °C:	<i>43 hPa</i>
Density and/or relative density	
Density at 20 °C:	<i>0.8 g/cm³</i>
Relative density	<i>Not determined.</i>
Vapour density	<i>Not determined.</i>
9.2 Other information	
Appearance:	
Form:	<i>Fluid</i>
Important information on protection of health and environment, and on safety.	
Ignition temperature:	<i>425 °C</i>
Explosive properties:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
Solvent content:	
Organic solvents:	<i>91.2 %</i>
Water:	<i>6.0 %</i>
VOC (EC)	<i>91.22 %</i>
Solids content:	<i>2.8 %</i>
Change in condition	
Evaporation rate	<i>Not determined.</i>
Information with regard to physical hazard classes	
Explosives	<i>Void</i>
Flammable gases	<i>Void</i>
Aerosols	<i>Void</i>
Oxidising gases	<i>Void</i>
Gases under pressure	<i>Void</i>
Flammable liquids	
<i>Highly flammable liquid and vapour.</i>	
Flammable solids	<i>Void</i>
Self-reactive substances and mixtures	<i>Void</i>
Pyrophoric liquids	<i>Void</i>
Pyrophoric solids	<i>Void</i>
Self-heating substances and mixtures	<i>Void</i>
Substances and mixtures, which emit flammable gases in contact with water	<i>Void</i>
Oxidising liquids	<i>Void</i>
Oxidising solids	<i>Void</i>
Organic peroxides	<i>Void</i>
Corrosive to metals	<i>Void</i>
Desensitised explosives	<i>Void</i>

SECTION 10: Stability and reactivity

10.1 Reactivity *No further relevant information available.*

(Contd. on page 6)

EU

Safety data sheet
according to 1907/2006/EC, Article 31 and 2020/878/EU

Printing date 12.08.2021

Version number 6 (replaces version 5)

Revision: 12.08.2021

Trade name: Kabelflussmittel ISO-Flux "KF-1"
Cable flux ISO-Flux "KF-1"

(Contd. of page 5)

10.2 Chemical stability**Thermal decomposition / conditions to be avoided:***No decomposition if used and stored according to specifications.***10.3 Possibility of hazardous reactions***Reacts with strong oxidising agents.**Forms flammable gases/fumes.***10.4 Conditions to avoid** *No further relevant information available.***10.5 Incompatible materials:** *No further relevant information available.***10.6 Hazardous decomposition products:** *Flammable gases/vapours***SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** *Based on available data, the classification criteria are not met.*

LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Oral	LD50	85,600 mg/kg

67-63-0 propan-2-ol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

Skin corrosion/irritation *Based on available data, the classification criteria are not met.***Serious eye damage/irritation***Causes serious eye irritation.***Respiratory or skin sensitisation** *Based on available data, the classification criteria are not met.***Germ cell mutagenicity** *Based on available data, the classification criteria are not met.***Carcinogenicity** *Based on available data, the classification criteria are not met.***Reproductive toxicity** *Based on available data, the classification criteria are not met.***STOT-single exposure***May cause drowsiness or dizziness.***STOT-repeated exposure** *Based on available data, the classification criteria are not met.***Aspiration hazard** *Based on available data, the classification criteria are not met.***11.2 Information on other hazards**

Endocrine disrupting properties
<i>None of the ingredients is listed.</i>

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:** *No further relevant information available.***12.2 Persistence and degradability** *No further relevant information available.***12.3 Bioaccumulative potential** *No further relevant information available.***12.4 Mobility in soil** *No further relevant information available.***12.5 Results of PBT and vPvB assessment****PBT:** *Not applicable.***vPvB:** *Not applicable.***12.6 Endocrine disrupting properties** *For information on endocrine disrupting properties see section 11.***12.7 Other adverse effects****Additional ecological information:****General notes:***Avoid transfer into the environment.**Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water**Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.***SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation***Must not be disposed together with household garbage. Do not allow product to reach sewage system.*

(Contd. on page 7)

EU

Safety data sheet
according to 1907/2006/EC, Article 31 and 2020/878/EU

Printing date 12.08.2021

Version number 6 (replaces version 5)

Revision: 12.08.2021

Trade name: Kabelflussmittel ISO-Flux "KF-1"
Cable flux ISO-Flux "KF-1"

(Contd. of page 6)

European waste catalogue

14 06 03*: other solvents and solvent mixtures

HP 3: Flammable

HP 4: Irritant - skin irritation and eye damage

HP 5: Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

cleaned sale packaging:

15 01 02: plastic packaging

overpack:

15 01 01: paper and cardboard packaging

Uncleaned packaging: 15 01 10*: packaging containing residues of or contaminated by hazardous substances**Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agents:** Water, if necessary together with cleansing agents.**SECTION 14: Transport information****14.1 UN number or ID number**

ADR, IMDG, IATA

UN1219

14.2 UN proper shipping name

ADR

1219 ISOPROPANOL (ISOPROPYL ALCOHOL)

IMDG, IATA

ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3 Transport hazard class(es)

ADR, IMDG, IATA

**Class**

3 Flammable liquids.

Label

3

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:**Marine pollutant:**

No

14.6 Special precautions for user

Warning: Flammable liquids.

Hazard identification number (Kemler code):

33

EMS Number:

F-E,S-E

Stowage Category

B

14.7 Maritime transport in bulk according to IMO**instruments**

Not applicable.

Transport/Additional information:**ADR****Limited quantities (LQ)**

1L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Transport category

2

Tunnel restriction code

D/E

IMDG**Limited quantities (LQ)**

1L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2012/18/EU**

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 8)

EU

Safety data sheet
according to 1907/2006/EC, Article 31 and 2020/878/EU

Printing date 12.08.2021

Version number 6 (replaces version 5)

Revision: 12.08.2021

Trade name: Kabelflussmittel ISO-Flux "KF-1"
Cable flux ISO-Flux "KF-1"

(Contd. of page 7)

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
<i>None of the ingredients is listed.</i>
REGULATION (EU) 2019/1148
Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
<i>None of the ingredients is listed.</i>
Annex II - REPORTABLE EXPLOSIVES PRECURSORS
<i>None of the ingredients is listed.</i>

National regulations:

Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reasons for changes:

16.06.2015: chapter 1 adaption to regulation 453/2010/EG Anhang II
03.11.2015: chapter 8, 15 adaption to regulation 830/2015/EU, 18/2012/EU
08.02.2017: chapter 8.2
03.05.2018: chapter 13, adaption to regulation 2016/913/EU
12.08.2021: chapter 1, 2, 3, 11, 15, 16

Information referred to in Annex I, point 1.3.4.2 of Regulation 1272/2008/EC:

Relevant phrases

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Contact: Dr. M. Probst

Version number of previous version: 5

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Safety data sheet SD3201

EU —